

CREST ROOFING TILES

# F12 Clay Pantile



F12 in  
Red Engobe (156)

**crest**  
BUILDING PRODUCTS

**30**  
Year  
Guarantee

t: 01430 432667

[www.crest-bst.co.uk](http://www.crest-bst.co.uk)

f: 01430 433000

e: [info@crest-bst.co.uk](mailto:info@crest-bst.co.uk)

Manufactured to comply with the requirements of EN1304 European Standard for Clay Roof Tiles

# F12 Double Interlocking Clay Pantile

▶ High quality clay tiles ▶ Minimum roof pitch 10° ▶ Economical ▶ Only 10 tiles per m<sup>2</sup>

## F12 Technical details:

Length	457mm
Width	286mm
Gauge	313-377mm
Cov' Width (mm)	235± 2.0
Min' roof pitch*	22°
No. of tiles per m <sup>2</sup>	11.7
Weight per tile	3.9 kg
Weight per m <sup>2</sup> (min.)	45.6 kg
Battens per m <sup>2</sup> (min)	2.3 - 2.6
Batten size (mm)	50 x 25
Fixing	Clipped

## A wide range of Fittings include:

F12  
Air ventilation tile



F12 Half round  
ridge (2.4 per m)



F12 Tapered  
ridge (2.6 per m)



## The F12 range of colours and fittings

The F12 double interlocking clay tile is available in eight different colours as below

F12 Brown gloss engobe (150)



F12 Copper engobe (142)



F12 Black engobe (141)



F12 Almond Brown (139)



F12 Anthracite (158)



F12 Red engobe (156)



F12 Dark Red gloss engobe (140)



F12 Black gloss engobe (120)

