

CREST ROOFING TILES

# F15 Clay Pantile



F15 Natural Red (115)

**30**  
Year  
Guarantee

**crest**  
BUILDING PRODUCTS

t: 01430 432667

[www.crest-bst.co.uk](http://www.crest-bst.co.uk)

f: 01430 433000

e: [info@crest-bst.co.uk](mailto:info@crest-bst.co.uk)

Manufactured to comply with the requirements of EN1304 European Standard for Clay Roof Tiles

# F15 Traditional Double Interlocking Clay Tile

▶ High quality clay tiles ▶ Minimum roof pitch 22° ▶ Economical ▶ Only 14.5 tiles per m<sup>2</sup>

## F15 Technical details:

Length	420mm
Width	261mm
Gauge	342-352mm
Cov' Width (mm)	199± 2.0
Min' roof pitch	22°
No. of tiles per m <sup>2</sup>	14.5
Weight per tile	3.1 kg
Weight per m <sup>2</sup> (min.)	44.9 kg
Battens per m <sup>2</sup> (min)	2.9
Batten size (mm)	50 x 25
Fixing	Clipped

## Fittings:

A wide choice of fittings are available including those below



**30**  
Year  
Guarantee

## The F15 range of colours and fittings

The F15 double interlocking clay tile is available in nine different colours as below



## Covering width dimensions

