

Declaration of Performance

053-00 / 083-00 / 026-00

Clay roof tiles and fittings

Tiles

F10 – F10Ü – F7 – H10 – H14 – H14GS – D10 – DS10 – R10 MS5 – DS5 – DS8 – G10 – G10S – G10new – S9
 Beavertail round cut 18/38 – Berlin beavertail segment cut 18.5/38
 Tower beavertail – Turret beavertail
 F12Pro – F12 Ü north - F12 Ü south – F13CL – F14 – H13 – D13 – R13S
 F15 – HZ16 – D15Ü – R15 – H15

For roof coverings on inclined roofs as well as outer wall claddings

Dachziegelwerke Nelskamp GmbH
Waldweg 6
46514 Schermbeck

Not applicable

System 4

Not applicable

Not applicable

Main features	Performance	Harmonised technical specification
Mechanical strength	Passed	EN 1304 (for edition of applicable standard, see front)
Performance under load from external fire	B _{ROOF} No test	
Fire performance	Category A1 to F	
Water impermeability	Fulfils Performance level 1 Test procedure 1 Test procedure 2	
Dimensions and variations in dimension	Passed	
Durability (Frost resistance)	Fulfils Test procedure E Performance level 1 (150 cycles)	

The performance of the product as per numbers 1 and 2 corresponds with the declared performance in accordance with number 9.

The responsibility for compiling this Declaration of Performance lies solely with the manufacturer as per number 4.

Signed for the manufacturer and in the name of the manufacturer by:

Schermbeck, 08th June 2020

Heinrich Nelskamp, CEO



Dachziegelwerke Nelskamp GmbH
Waldweg 6
46514 Schermbeck

2020

Clay roof tiles and fittings

EN 1304 (see front)

053-00 / 083-00 / 026-00

Clay roof tiles and fittings for roof coverings and outer wall claddings

Mechanical strength	Passed
Performance under load from external fire	B _{ROOF} No test
Fire performance	Category A1 to F
Water impermeability	Fulfils Performance level 1 Test procedure 2
Dimensions and variations in dimension	Passed
Durability (Frost resistance)	Fulfils Test procedure E Performance level (150 cycles)