


**NELISSEN**

## Declaration of performance



Number	NEHVB016_2_EN_21084		
Product type / CE	OLD RYEDALE		
Intended use or uses of the construction product	Units for use in unprotected masonry walls, columns and partitions.		
Manufacturer	Nelissen Steenfabrieken NV Kiezelweg 460 B-3620 Lanaken		Tel: +32 (0)12 44 02 44 Fax: +32 (0)12 45 53 89 info@nelissen.be
System or systems of assessment and verification of constancy of performance of the construction product	2+		
Notified body	BCCA NB 0749		
Harmonized standard	EN 771-1:2011 +A1:2015		

Notified Body performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.

## Declared performance

For available sizes refer to the product sheet and / or website.

Dimensions		M50	M65	N70/4	N70/5	N70/7	NNF	RF	WV50	WV65	
Length	(mm)	188	188	239	239	240	241	208	209	213	
Width	(mm)	88	88	72	72	70	108	100	100	101	
Height	(mm)	51	64	40	50	70	73	40	49	65	
Compressive strength.	(N/mm²)	Cat. I , ⊥	22	25	15	24	26	26	22	22	25
Mean compressive strength	(N/mm²)		30	30	20	30	30	30	30	30	30
Tolerance category						T2					
Range category						R1					
Flatness of bed faces						NPD					
Plane parallelism of bed faces						NPD					
Gross dry density						1630(D1)			Kg/m³		
Net dry density						NPD			Kg/m³		
Configuration						1					
Bond strength						NPD			N/mm²		
Thermal conductivity						(λ10,dry,mat(90,90))			0,59 (S2)		W/mK
Thermal conductivity						(λ10,dry,mat) EN1745 Annex A			0,55 (S1)		W/mK
Water vapour permeability									5/10		
Freeze/Thaw resistance									F2		
Water absorption									14		%
Initial water absorption									1,5<IW<=4		Kg/(m².min)
Active soluble salts									S2		
Dimensional stability: moisture expansion									NPD		Mm/m
Reaction to fire									A1		
Dangerous substances									NPD		

The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above.

Signed for and on behalf of the manufacturer by

Burt Nelissen (General Management)

Lanaken (B)

25.03.2021