

CREST NELSKAMP ROOFING TILES

D15u clay pantile



D15u Natural Red



crest
NELSKAMP
ROOFING TILES

t: 01430 432667

www.crest-bst.co.uk

e: info@crest-bst.co.uk

Manufactured to comply with the requirements of EN1304 European Standard for Clay Roof Tiles

D15u Interlocking Clay Pantile

► High quality clay tiles ► Minimum roof pitch 15° ► Economical ► Only 14.4 tiles per m²

D15u Technical details:

Length	420 mm
Width	252 mm
Gauge	336-352 mm
Cov' Width (mm)	208 ± 1.0
Min' roof pitch*	15°
No. of tiles per m ²	13.7-14.4
Weight per tile	3.1 kg
Weight per m ² (min.)	42.47 kg
Batten size (mm)	50 x 25
Fixing	Clipped

Fittings Include:

D15u Half round interlocking ridge (3.0 per m)



D15u Hip Starter



D15u Starter Ridge



D15u End Ridge



D15u Half Tile



D15u Left Hand and Right Hand Cloaked Verge Tiles



The D15u range of colours

D15u Natural Red (115)



D15u Blue Reduced (144)



D15u Matt Black Engobe (133)



D15u Black Engobe (119)



To overcome any minor shade variations inherent in the production of natural clay products, we recommend that tiles are mixed from at least 3 pallets on site. The colours shown here are only as accurate as allowed for by the printing process. Product samples are available on request.

crest
NELSKAMP
ROOFING TILES



For more information on the H15 or to order a sample call us on **01430 432667**

www.crest-bst.co.uk