

Declaration of Performance		
026-00		
Clay roof tiles and fittings		
Tiles F15 – HZ16 – D15Ü – R15 – H15		
For roof coverings on inclined roofs as well as outer wall claddings		
Dachziegelwerke Nelskamp GmbH Waldweg 6 46514 Schermbeck		
Not applicable		
System 4		
Not applicable		
Not applicable		
Main features	Performance	Harmonised technical specification
Mechanical strength	Passed	EN 1304 (for edition of applicable standard, see front)
Performance under stress from external fire	B <sub>ROOF</sub> No test	
Fire performance	Category A1 to F	
Water impermeability	Fulfils Performance level 1 Test procedure 1 Test procedure 2	
Dimensions and variations in dimension	Passed	
Durability (Frost resistance)	Fulfils Test procedure E Performance level 1 (150 cycles)	


10


The performance of the product as per numbers 1 and 2 corresponds with the declared performance in accordance with number 9.

The responsibility for compiling this Declaration of Performance lies solely with the manufacturer as per number 4.

Signed for the manufacturer and in the name of the manufacturer by:

Schermbeck, 25.04.13

  
Dipl.-Ing. Manfred Bracht,  
Managing Director

	
<b>Dachziegelwerke Nelskamp GmbH Waldweg 6 46514 Schermbeck</b>	
<b>2013</b>	
Clay roof tiles and fittings	
EN 1304 (see front)	
<b>026-00</b>	
Clay roof tiles and fittings for roof coverings and outer wall claddings	
Mechanical strength	Passed
Performance under load from external fire	B <sub>ROOF</sub> No test
Fire performance	Category A1 to F
<b>Water impermeability</b>	Fulfils Performance level 1 Test procedure 2
Dimensions and variations in dimension	Passed
Durability (Frost resistance)	Fulfils Test procedure E Performance level (150 cycles)