

CREST NELSKAMP ROOFING TILES

H14 clay pantile



H14
in Natural Red



crest
NELSKAMP
ROOFING TILES

t: 01430 432667

www.crest-bst.co.uk

e: info@crest-bst.co.uk

Manufactured to comply with the requirements of EN1304 European Standard for Clay Roof Tiles

H14 Traditional Double Interlocking Clay Tile

▶ High quality clay tiles ▶ Minimum roof pitch 10° ▶ Economical ▶ Only 13.9 tiles per m²

H14 Technical details

Length	434 mm
Width	267 mm
Gauge	323-343 mm
Cov' Width (mm)	215 ± 2.0
Min' roof pitch*	10°
No. of tiles per m ²	13.9
Weight per tile	3.7 kg
Weight per m ² (min.)	51.4 kg
Battens per m ² (min)	3.0
Batten size (mm)	50 x 25
Fixing	Clipped

Fittings: A wide choice of fittings are available including these below

Tile Clip

H14 Tapered ridge tile
(2.6 per m)



H14 Double roll tile



Crest Tile Clip

H14 Starter ridge tile



H14 End ridge tile



H14 Cloaked verge tiles (left and right hand)



Low roof pitches 17°-10°

H14 is the perfect interlocking clay pantile for low-pitch roofs, we recommend that these fixing practices are followed:

- Lay H14 tiles straight bond
- Headlap minimum 100mm
- Use appropriate air and vapour permeable underlay, which does not require secondary roof ventilation.
- Lay the roof underlay to the manufacturer's instructions
- Maximum rafter length 6m
- All tiles are to be clipped with purpose-made tile clips, reference 409/223
- Roof perimeters including around roof windows must be securely fixed to BS 5534
- All areas around the roof perimeter and abutments must be properly finished as well as any areas around any 'velux type' windows (These are the areas where potential problems are likely to occur on a low roof pitch.)

The H14 range of colours

Natural Red (201)



Red Brown (202)



Black Engobe (232)



Matt Black (239)



Black Gloss (218)



crest
NELSKAMP
ROOFING TILES



For more information on the H14 Tile or to order a sample call us on **01430 432667**