# F12 Clay Pantile







t: 01430 432667

www.crest-bst.co.uk

e: info@crest-bst.co.uk

## F12 Double Interlocking Clay Pantile

► High quality clay tiles ► \*Minimum roof pitch 10° ► Economical ► Only 12 tiles per m²

F12 Technical details:	
Length	457mm
Width	286mm
Gauge	313-377mm
Cov' Width (mm)	235± 2.0
Min' roof pitch*	10°
No. of tiles per m <sup>2</sup>	11.7
Weight per tile	3.9 kg
Weight per m <sup>2</sup> (min.)	45.6 kg
Battens per m <sup>2</sup> (min)	2.3 - 2.6
Batten size (mm)	50 x 25
Fixing	Clipped

<sup>\*</sup>Please consult Crest for roof pitches between 22° - 10°

#### A wide range of Fittings include:

F12 Left Hand Cloaked Verge









### The F12 range of colours and fittings

The F12 double interlocking clay tile is available in six different colours as below

#### Low roof pitches 17°-10°

F12 is the perfect interlocking large clay pantile for low-pitch roofs, we recommend that these fixing practices are followed:

- Lay F12 tiles straight bond.
- Headlap minimum 100mm.
- Use appropriate air and vapour permeable underlay, which does not require secondary roof ventilation.
- Lay the roof underlay to the manufacturer's instructions.
- Maximum rafter length 6m.
- All tiles are to be clipped with purpose-made tile clips, reference 409/002
- Roof perimeters including around roof windows must be securely fixed to BS 5534
- All areas around the roof perimeter and abutments must be properly finished as well as any areas around any 'velux type' windows (These are the areas where potential problems are likely to occur on a low roof pitch.)

F12 Red engobe (156)



F12 Copper engobe (142)



F12 Dark Red gloss engobe (140)



F12 Anthracite (158)



F12 Black engobe (141)



F12 Black gloss engobe (120)







