



# The Double Roman

HIGH QUALITY CONCRETE



FINISH  
**TOP ONE**

**The Crest Double Roman sets a new standard for these tiles which everyone from Architects to Roofers appreciate..**

The Double Roman is superbly crafted with its classic, timeless shape and the design is perfectly enhanced by the rounded trimmed edge to enhance the finished roof.

With a covering capacity of just 9.7 tiles per square metre it also makes the Double Roman the perfect choice for a very economical and attractive roof. These Double Roman tiles are engineered to the highest of standards and are available in six different colours with silk coatings and benefit from a wide range of fittings.

**crest**  
**NELSKAMP**  
**ROOFING TILES**

Order your **FREE** roof tile sample email: [samples@crest-bst.co.uk](mailto:samples@crest-bst.co.uk)

01430 432667 [info@crest-bst.co.uk](mailto:info@crest-bst.co.uk) [www.crest-bst.co.uk](http://www.crest-bst.co.uk)

# The Double Roman Concrete Tile

A long established Roman design popular in most regions, ideal for any type of project.



## Double Roman technical details

Length:	420mm
Width:	332mm
Gauge:	310 - 345mm
Headlap (min):	75mm (22.5°+), 100mm (17.5°+), 110mm (15°+)
Cover width (mm):	300mm ± 2.0
Minimum roof pitch*:	15° @110mm headlap
Number of tiles per m <sup>2</sup> (min):	9.7
Weight per tile:	4.4 kg
Weight per m <sup>2</sup> (min):	44 kg
Battens per m <sup>2</sup> (min):	3 - 3.2
Batten size (mm):	50 x 25 - 600mm centres
Fixings clips:	Eaves and tile clips
Nails - ring shank aluminium alloy:	45 x 3.35mm
Screw - with neoprene washer seal:	45 x 4.5mm

Please Note: Fixing specs may vary due to roof pitch and location

## Double Roman range available in 6 colours



## Low Pitch Roof Specification 17° - 15°

- Lay Double Roman straight bond.
- Headlap minimum 110mm.
- Use appropriate air and vapour permeable underlay, which does not require secondary roof ventilation.
- Lay the roof underlay to the manufacturer's instructions.
- Maximum rafter length 7.5m.
- All tiles to be clipped with Crest purpose made tile clips, reference 409/001. Do not nail the tiles at 17° and below.
- Roof perimeters including, abutments and around roof windows must be securely fixed to BS 5534.
- Further Low Pitch Roofing Advice is available on our website.

## Double Roman tile fittings



FOR MORE FITTINGS VISIT OUR WEBSITE

- ▶ Superior Quality Double Pantile ▶ Eco friendly Top One finish
- ▶ Cleaner, Smooth Round Trimmed Edges ▶ Only 9.7 tiles per m<sup>2</sup>
- ▶ Range of Colours & Quality Fittings

Manufactured to comply with the performance standards of EN490/491 and DIN Plus



For more information on our **Concrete** tiles or to order a **FREE** sample call us on **01430 432667**

☎ 01430 432667 ✉ info@crest-bst.co.uk 🌐 www.crest-bst.co.uk

