

# G10 PRO SMOOTH FLAT CLAY ROOF TILE

HIGH QUALITY CLAY TILES FOR EVERY PROJECT INCLUDING LOW PITCH



The **G10 PRO** Flat Clay Roofing Tile is a large format **double interlocking** flat clay tile that is available in a range of colours, finishes and fittings.

G10 PRO  
BLACK  
ENGOBE



## THE G10 PRO LARGE FORMAT CLAY TILE



These tiles are superbly engineered and designed for a quick, easy and secure installation and are ideal for use with low pitch roofs. The G10 PRO can also be used for vertical cladding on walls and façade.

With a covering capacity of only 10 tiles per square metre, this allows the G10 PRO Flat Clay Roofing Tile to be installed very economically. The G10 PRO is an ideal tile for low pitch roofs and can even be used as a cost effective alternative to vertical cladding systems. Like all Crest Nelskamp tiles the G10 PRO flat clay roofing tile is available with a wide range of fittings.

- **High quality clay tile**
- **Minimum roof pitch 10°**
- **Long term durability**
- **Eco friendly**
- **Low maintenance**
- **Wide range of colours & fittings**
- **Only 10 tiles per m<sup>2</sup>**
- **Quick, easy & secure installation**

Whatever your needs, from traditional rustic pantiles to beautiful large format clay tiles and crafted glazed tiles, we have a wide choice of roofing materials all proven to compliment any type of project.

Throughout this brochure on the G10 PRO you should find most of the details you need, however if you require more information on this or any other product please don't hesitate to call us on 01430 432 667.

## LARGE FORMAT DOUBLE INTERLOCKING . . .

## TECHNICAL DATA

Length ~ 488 mm.
Width ~ 297 mm.
Gauge ~ 386 mm to 406 mm.
Covering Width ~ 250 mm ± 1.0 mm.
Minimum low roof pitch ~ 10°
Number of tiles per m <sup>2</sup> ~ 9.9 - 10.4 pcs
Weight per tile ~ 4.5 kg.
Weight per m <sup>2</sup> (min.) ~ 44.55 kg.
Battens required per m <sup>2</sup> (min) ~ 2.5
Batten size (mm) ~ 50 x 25
Fixing ~ Clipped

## LOW PITCHES 17°-10°

- Use appropriate air and vapour permeable underlay, which does not require secondary roof ventilation.
- Lay the roof underlay to the manufacturer's instructions.
- Lay G10 tiles broken bond.
- Headlap minimum 100mm.
- Maximum rafter length 6m.
- All tiles are to be clipped with purpose-made tile clips, reference 409/215
- Left Hand Verge tiles are to be fixed with 45mm tile fixing screw with a neoprene washer, also fix verge clips if mortar bedding the verge.
- Roof perimeters including around roof windows must be securely fixed to BS 5534.
- Further low pitch roofing advice available on our website.



## COLOUR AVAILABILITY

G10 PRO range of colours and finishes.



Natural Red



Red Brown



Slate Grey (available on request)



Matt Black



Black Gloss



Black Engobe

## Colour deviations:

Our clay roofing tiles are environment-friendly building materials. When using natural raw materials you may experience colour deviations. This is often the case with naturally red tiles since the fired colour is the sole result of natural raw materials with no added metal oxides to change the colour.

Deviations are also possible in the colours for reasons and limitations relating to printing methods. Clay roof tile surfaces: Minor impairments to the surface are possible due to transport or site handling. This does not effect the overall quality or performance of the tiles. (Jan 2026)



## Technical Support



Need help with your roof?  
Please contact our team of  
experienced professionals.

## Customer Service



Telephone: 01430 432 667

Opening times:  
Mon - Fri: 8.30am to 5.00pm

## Nelskamp Guarantee



Complete peace of mind  
with our 30 year guarantee  
Ask for details.

Crest are members of the  
Builders Merchants Federation  
and UFEMAT



### Head Office:

Crest Building Products  
Howdenshire Way  
Howden  
East Yorkshire  
DN14 7HZ

01430 432 667

info@crest-bst.co.uk

[www.crest-bst.co.uk](http://www.crest-bst.co.uk)

**crest**  
NELSKAMP  
ROOFING TILES

## G10 PRO ACCESSORIES

### CLAY FITTINGS, RIDGES AND SPECIAL TILES

Crest Nelskamp manufacture a wide selection of clay roof tile fittings and accessories.

The G10 PRO special tiles are available in a selection of colours designed to match your roof.

For further details please call us on 01430 432 667.

#### STANDARD TILES AND VERGE TILE FITTINGS



Standard Tile



Half Tile  
Right hand tile




Double Roll  
Left hand verge finishing tile



Half Double Roll  
Left hand verge finishing tile

All sizes are approx. Tolerances  
according to DIN EN 1304.  
Covering sizes are to be  
determined on site.  
Subject to technical changes.




Left Hand Cloaked Verge



Right Hand Cloaked Verge



Half Left Hand Cloaked Verge




Half Right Hand Cloaked Verge

#### RIDGE AND HIP TILES



Standard Tapered Ridge  
(2.7 pc/m)




Standard Starter Ridge



Standard End Ridge



Standard Hip Starter



Universal Hip Junction



Angled Ridge (2.6 pc/m)



Angled Ridge Starter




Angled Ridge End




Angled Ridge Block End

#### SPECIAL TILES



External Mansard



Internal Mansard



Mono Ridge



Ventilation Tile

Low pitch vent tile also available for 17° to 15°

#### FIXINGS



Fixing Clip  
No. 409/234



Ridge Clip  
No. 470/41 for standard ridge tile



Universal Eave Clip  
No. 436a



Verge Clip



Left hand verge tiles are to be fixed  
with 45mm screw with neoprene washer

#### DRY FIX SYSTEM



#### Necoroll dry fix system for ridge and hip

Faster, cleaner, more effective solutions for all roofs.

The highest quality aluminium ridge roll using the latest  
micro-ventilation technology. Provides excellent protection  
and ridge and ridge ventilation.



*Creative Roofscaping*

For more information on our **roofing tiles** or to order  
a **FREE** tile sample contact the Crest team today.

[www.crest-bst.co.uk](http://www.crest-bst.co.uk)